


## Tapered roller bearing 65200-65500-TIMKEN - 65200-65500-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/65200-65500-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
52 800	127 800	44 450	242000	1.23	62100	52700	1.20	297000	65200	65500
2 032	5 000	1 750	54700		14200	11900		66700		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. r <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>						
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
1 750	34 925	-0.4	3.5	68.8	25.8	3.3	119.8	107.8	4.1	1.1	85.2	17.2	0.9027	2.90
			0.14	2.72	2.95	0.13	4.89	4.21	0.16	0.05				6.38

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952316529
Inside diameter	50.8 mm
Inside diameter	2" inch
Outside diameter	127 mm
Outside diameter	5" inch
Thickness	44.45 mm
Thickness	1 3/4" inch
Weight	2900 g
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE