


## Tapered roller bearing 622A-612A-TIMKEN - 622A-612A-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/622a-612a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer		
mm	mm	mm	N		N	N	N				
55.006	120.040	41.275	201900	0.31	1.01	53900	20900	1.66	244000	622A	612A
2.1850	4.7260	1.6250	48500			12100	6510		54800		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width		Shaft		Housing		Cage								
B	C	ER. Dr. r <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
mm	mm	mm	mm	mm	mm	mm	mm	mm				kg		
41.275	31.750	-14.6	0.8	64.8	65.8	3.3	119.8	193.8	3.8	1.9	75.9	16.2	0.9064	2.13
1.6250	1.2500	-0.58	0.03	2.52	2.58	0.13	4.33	4.06	0.15	0.09				4.72

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952317595
Inside diameter	55.006 mm
Outside diameter	120.04 mm
Thickness	41.275 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE