


## Tapered roller bearing 95475-95925-TIMKEN - 95475-95925-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/95475-95925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
120.650	234.950	63.500	62900	0.37	162000	153000	1.58	95475	95925	
4.750	9.250	2.500	141000		36700	22000				

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				Ag		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
63.500	48.212	-14.8	0.4	137.0	148.6	3.3	217.0	200.0	6.4	3.8	453.9	98.4	0.1323	12.35
2.900	1.5275	-0.35	0.25	5.20	5.87	0.13	9.94	8.23	0.25	0.15				27.25

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952324975
Inside diameter	120.65 mm
Outside diameter	234.95 mm
Thickness	63.5 mm
Weight	12400 g
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE