

## Tapered roller bearing 95512X-95925-TIMKEN - 95512X-95925-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/95512x-95925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N	N				
130.000	234.950	63.500	62900	1.62	103000	193000	1.58	937000	95512X	95925
5.1181	9.2500	2.5000	141000		36700	22000		209000		

  

Bearing Dimensions										Geometry Factors			Bearing Weights	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. r <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>						
63.500	48.212	-14.8	0.8	145.0	156.6	3.3	217.8	200.0	6.4	3.8	453.9	98.4	0.1023	15.44
2.5000	1.9375	-0.58	0.24	5.71	6.14	0.13	8.54	8.23	0.25	0.15				25.24

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952325309
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	234.95 mm
Outside diameter	9 1/4" inch
Thickness	63.5 mm
Thickness	2 1/2" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE