


# Tapered roller bearing LL660749A-LL660711-TIMKEN - LL660749A-LL660711-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/ll660749a-ll660711-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> e	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
338.138	403.225	33.338	301900	0.42	78190	1.42	827900	LL660749A	LL660711	
13.3125	15.8750	1.3125	67700		17600		186000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. r <sup>1)</sup>	Max Shaft Fillet Radius R <sup>2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>4)</sup>	A <sub>2</sub> <sup>5)</sup>						
33.338	26.988	33.3	3.3	390.0	33.0	3.3	394.0	380.0	1.8	1.8	1790.4	197.8	0.2095	7.63
1.3125	1.0625	1.31	0.13	13.78	13.00	0.13	15.51	15.20	0.07	0.04				16.83

## PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952329659
Inside diameter	338.138 mm
Inside diameter	13 5/16" inch
Outside diameter	403.225 mm
Outside diameter	15 7/8" inch
Thickness	33.338 mm
Thickness	1 5/16" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE