


## Tapered roller bearing 395-3920-B-TIMKEN - 395-3920-B-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/395-3920-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**



| Bearing Dimensions |           |            |  | Load Ratings                |  |                             |                          |       |       | Part Number |  |
|--------------------|-----------|------------|--|-----------------------------|--|-----------------------------|--------------------------|-------|-------|-------------|--|
| Bore<br>d          | O.D.<br>D | Width<br>B | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factors <sup>(2)</sup><br>e | Dynamic <sup>(1)</sup><br>C <sub>2</sub> | Factors <sup>(2)</sup><br>K | Static<br>C <sub>3</sub> | Inner | Outer |             |  |
| mm                 | mm        | mm         | N  |                             | N  |                             | N                        |       |       |             |  |
| 63.500             | 112.712   | 21.917     | 9800                                     | 0.45                        | 1.45                                     | 23000                       | 17000                    | 12500 | 305   | 3620-B      |  |
| 2.500              | 4.4275    | 0.2117     | 22200                                    |                             | 5700                                     | 3570                        | 26100                    |       |       |             |  |

| Bearing Dimensions |            |                               |                                    |                                   |  | Shaft                                      |  |  | Housing        |                | Geometry Factors |                |                | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|----------------|----------------|----------------|
| Width<br>B         | Width<br>C | Eff. Ctr.<br>a <sup>(1)</sup> | Outer Ring<br>Range D <sub>1</sub> | Flange<br>Width<br>C <sub>1</sub> | Max Shaft<br>File Radius<br>R <sup>(1)</sup> | Sealing<br>Shoulder Dia.<br>d <sub>1</sub> | Sealing<br>Shoulder Dia.<br>d <sub>2</sub> | Sealing<br>Shoulder Dia.<br>D <sub>1</sub> | D <sub>1</sub> | D <sub>2</sub> | C <sub>1</sub>   | C <sub>2</sub> | C <sub>3</sub> | kg             |
| mm                 | mm         | mm                            | mm                                 | mm                                | mm   | mm   | mm   | mm   | mm             | mm             | mm               | mm             | mm             | lbs            |
| 21.906             | 22.812     | -4.8                          | 112.270                            | 4.762                             | 3.5  | 76.6                                       | 77.8                                       | 108.8                                      | 58.0           | 21.4           | 0.0984           | 1.96           | 4.32           | 2.32           |
| 0.8600             | 0.9075     | -0.03                         | 4.4275                             | 0.1875                            | 0.14   | 2.78                                       | 3.02                                       | 4.25                                       |                |                |                  |                |                |                |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | TIMKEN        |
| N° Ean13         | 3663952338408 |
| Inside diameter  | 63.5 mm       |
| Outside diameter | 112.712 mm    |
| Thickness        | 21.996 mm     |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE