



## Tapered roller bearing 941-932-B-TIMKEN - 941-932-B-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/941-932-b-timken>

| TAPERED ROLLER BEARINGS                                                           |         |                            |                                                                                   |                             |                                          |                                       |                                       |                                                               |                                                                                    |              |        |       |  |             |  |
|-----------------------------------------------------------------------------------|---------|----------------------------|-----------------------------------------------------------------------------------|-----------------------------|------------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|--------|-------|--|-------------|--|
| TYPE TSF                                                                          |         |                            |                                                                                   |                             |                                          |                                       |                                       |                                                               |                                                                                    |              |        |       |  |             |  |
|  |         |                            |  |                             |                                          |                                       |                                       |                                                               |  |              |        |       |  |             |  |
| Bearing Dimensions                                                                |         |                            |                                                                                   |                             |                                          |                                       |                                       |                                                               |                                                                                    | Load Ratings |        |       |  | Part Number |  |
| Bore #                                                                            | O.D. D  | Width T <sub>1</sub>       | Dynamic <sup>(1)</sup> C <sub>1</sub>                                             | Factors <sup>(2)</sup> e    | Y                                        | Dynamic <sup>(1)</sup> C <sub>2</sub> | Factors <sup>(2)</sup> e <sub>2</sub> | K                                                             | Static C <sub>3</sub>                                                              | Inner        | Outer  |       |  |             |  |
| mm                                                                                | mm      | mm                         | N                                                                                 |                             |                                          | N                                     |                                       |                                                               | N                                                                                  |              |        |       |  |             |  |
| 101.600                                                                           | 212.725 | 23.812                     | 572000                                                                            | 0.35                        | 0.34                                     | 148000                                | 82700                                 | 1.79                                                          | 780000                                                                             | 941          | 932-B  |       |  |             |  |
| 4.000                                                                             | 8.375   | 0.9375                     | 126000                                                                            |                             |                                          | 33000                                 | 16600                                 |                                                               | 175000                                                                             |              |        |       |  |             |  |
| Bearing Dimensions                                                                |         |                            |                                                                                   |                             |                                          |                                       |                                       |                                                               |                                                                                    |              |        |       |  |             |  |
| Width B                                                                           | Width C | Eff. Ctr. a <sup>(3)</sup> | Outer Ring Flange O.D. D <sub>1</sub>                                             | Flange Width C <sub>2</sub> | Max Shaft Fillet Radius R <sup>(4)</sup> | Sealing Shoulder Dia. d <sub>1</sub>  | Sealing Shoulder Dia. d <sub>2</sub>  | Geometry Factors G <sub>1</sub> G <sub>2</sub> C <sub>3</sub> | Bearing Weight                                                                     |              |        |       |  |             |  |
| mm                                                                                | mm      | mm                         | mm                                                                                | mm                          | mm                                       | mm                                    | mm                                    |                                                               | kg                                                                                 | lbs.         |        |       |  |             |  |
| 66.675                                                                            | 52.975  | -18.8                      | 223.700                                                                           | 11.112                      | 7.5                                      | 112.0                                 | 130.0                                 | 198.0                                                         | 338.6                                                                              | 28.6         | 0.1103 | 11.33 |  |             |  |
| 2.6250                                                                            | 2.1250  | -0.75                      | 8.8085                                                                            | 0.4375                      | 0.29                                     | 4.41                                  | 5.12                                  | 7.83                                                          |                                                                                    |              |        |       |  |             |  |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | TIMKEN        |
| N° Ean13         | 3663952339665 |
| Inside diameter  | 101.6 mm      |
| Outside diameter | 212.725 mm    |
| Thickness        | 66.675 mm     |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE