

# Tapered roller bearing L357040-L357019-B-TIMKEN - L357040-L357019-B-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/l357040-l357019-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**

Bearing Dimensions										Load Ratings				Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factors <sup>(2)</sup> e	Y	Dynamic <sup>(1)</sup> C <sub>90</sub>	Factors <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer					
mm	mm	mm	N			N		N							
289.975	404.950	22.225	50600	0.30	1.10	152000	9300	1310000	L357040	L357019-B					
11.4163	15.9431	0.8750	12200			34000	2100	295000							

  

Bearing Dimensions										Shaft			Housing			Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(1)</sup>	Outer Ring Flange D <sub>1</sub>	Flange Width C <sub>1</sub>	Max Shaft Fillet Radius R <sup>(2)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. d <sub>3</sub>	Sealing Shoulder Dia. d <sub>4</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>					kg		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm										
22.225	38.100	12.7	418.822	9.525	6.4	288.0	218.0	288.0	175.3	201.0	0.1585						20.08		
0.8750	1.5000	0.50	16.5324	0.3750	0.25	12.13	12.52	14.98									44.25		

## PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952340708
Inside diameter	289.975 mm
Inside diameter	11.416" inch
Outside diameter	404.95 mm
Outside diameter	15.943" inch
Thickness	50.8 mm
Thickness	2" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE