


Deep groove ball bearing single row 1217-K-TVH-C3-H217-FAG - 1217-K-TVH-C3-H217-FAG

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/1217-k-tvh-c3-h217-fag>

Self-aligning ball bearings 1217-K-TVH-C3 + H217
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



d_w	75 mm
D	150 mm
B	28 mm
B_{min}	6 mm
c	18 mm
D_i	130,4 mm
D_o_{max}	139 mm
D_o	110 mm
d	85 mm
d_i	107,5 mm
d_o_{max}	96 mm
d_o	90 mm
l	50 mm
$r_{a_{max}}$	2 mm
H217	Mass, adapter sleeve
m	2,03 kg Mass
m	1,03 kg Mass, adapter sleeve
C	49500 N Basic dynamic load rating, radial
e	0,17
Y_1	3,73
Y_2	5,78
C_0	20800 N Basic static load rating, radial
Y_0	3,91
n_c	4800 1/min Limiting speed
n_R	6700 1/min Reference speed
C_{-1}	1180 N Fatigue limit load, radial

PRODUCT FEATURES

Brand	FAG
N° Ean13	3663952346281
Inside diameter	75 mm
Outside diameter	150 mm
Thickness	28 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE