




Tapered roller bearing 33112-TIMKEN - 33112-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/33112-timken>

TAPERED ROLLER BEARINGS														
SINGLE-ROW • IsoClass														
IsoClass														
														
Bearing Dimensions			Load Ratings						Part Number					
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾		Factor ⁽²⁾ e	Dynamic ⁽³⁾		Factor ⁽²⁾ K	Static C ₀	Assembly Inner/Outer				
mm	mm	mm	N	N		N	N		N					
in	in	in	lbf	lbf		lbf	lbf		lbf					
60.000	100.000	30.000	142000	670	1.31	42000	26000	1.47	189000	33112				
2.3622	3.9370	1.1811	31400			9440	5840		42500					
Bearing Dimensions														
Shaft			Housing				Cage		Geometry Factors			Bearing Weight		
Width B	Width C	ER Dr. a ⁽⁴⁾	Max Shaft Fillet Radius R ⁽⁵⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽⁶⁾	Backing Shoulder Dia. D _s	D _s	A ₁ ⁽⁷⁾	A ₂ ⁽⁷⁾	G ₁	G ₂	C ₃	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
in	in	in	in	in	in	in	in	in	in	in	in	in	lb	
30.000	23.000	-0.4	1.5	47.0	22.0	1.5	86.0	90.0	2.4	2.0	61.7	23.9	0.1021	0.85
1.1811	0.9093	-0.25	0.06	2.94	2.83	0.06	3.38	3.54	0.09	0.10				2.00

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	53893276878
Inside diameter	60 mm
Outside diameter	100 mm
Thickness	30 mm
Weight	924 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE