

## Tapered roller bearing 32930-TIMKEN - 32930-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32930-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
in	in	in	lbf		lbf		lbf			
150.000	210.000	38.000	524000	0.33	849000	1.78	579000	2030		
5.905	8.2677	1.4961	128500		189000		129000			

  

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
in	in	in	in	in	in	in	in	in	in	in	in	in	lb	
38.000	36.000	-1.5	2.5	160.0	160.0	2.0	200.0	197.0	1.5	2.0	428.9	151.2	0.1167	3.88
1.4961	1.4173	-0.06	0.10	6.30	6.30	0.08	7.87	7.76	0.06	0.08	16.88	5.95	0.0046	0.11

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354040
Inside diameter	150 mm
Outside diameter	210 mm
Thickness	38 mm
Weight	4000 g
Packaging	-
Standard	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE