

## Tapered roller bearing 32032X-TIMKEN - 32032X-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32032x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup>		Factor <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Static C <sub>0</sub>	
mm	mm	mm	C <sub>1</sub>	e	C <sub>2</sub>	K	C <sub>10</sub>	N	N	N
in	in	in	in		in		in	in	in	in
160.000	240.000	51.000	480000	0.16	1.27	125000	5700	1.27	833000	132000
6.2992	9.4488	2.0079	108000			28000	22500			

  

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a <sup>(4)</sup>	Max Shaft Fillet Radius R <sup>(5)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(6)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(7)</sup>	A <sub>2</sub> <sup>(8)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
in	in	in	in	in	in	in	in	in	in	in	in	in	lbs	
160.000	240.000	1.8	3.0	176.0	191.0	2.5	124.0	121.0	3.5	4.1	101.7	123.0	0.1106	7.85
2.0079	1.4961	0.07	0.12	6.89	7.13	0.10	9.21	8.70	0.13	0.16				17.21

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354071
Inside diameter	160 mm
Outside diameter	240 mm
Thickness	51 mm
Weight	7750 g
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE