

## Tapered roller bearing 32968-TIMKEN - 32968-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32968-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in	in	in	lbf		lbf	lbf	lbf			
340.000	460.000	76.000	1220000	0.04	216000	227000	1.34	2040000	32968	
13.386	18.112	2.992	274000		71000	52300		5940000		

  

Steering Dimensions										Geometry Factors			Bearing Weight		
Drift					Housing					Cage					
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Shoulder Dia. d <sub>e</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lbs
34.000	57.000	14.7	4.0	300.0	300.0	3.0	480.0	402.0	16.5	4.3	2703.6	309.5	0.1967	24.40	
2.992	2.244	0.58	0.16	14.13	14.12	0.12	17.58	13.21	0.61	0.17				75.56	

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354224
Inside diameter	340 mm
Inside diameter	13.386" inch
Outside diameter	460 mm
Outside diameter	18.11" inch
Thickness	76 mm
Thickness	2.992" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)  
02038 087 274  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE