

Drawn cup roller bearing TLAM3018-IKO - TLAM3018-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/tlam3018-iko>



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
	30	---	---							

F _w	D	C	r ₁ Max.	Standard reporting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
				Shaft dia. h8		Housing bore dia. H7							
				Max.	Min.	Max.	Min.						
30	37	18	2.8	30.000	29.987	---	---	36.992	36.987	16 400	29 800	12 000	---

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952355115
Inside diameter	30 mm
Outside diameter	37 mm
Thickness	18 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE