

## Tapered roller bearing 44162-44363D-TIMKEN - 44162-44363D-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/44162-44363d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Factor <sup>(4)</sup>	
mm	mm	mm	mm	C <sub>10</sub>	C	N <sub>10</sub>	N	C <sub>90</sub>	C <sub>50</sub>	C <sub>100</sub>	K
41.275	92.075	55.562	36.688	17400	0.78	0.86	1.25	25000	34000	45000	0.75
1.6200	3.6250	2.1875	1.5625	38100				5810	7770	10100	

  

Part Number		Dimensions						Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>		
44162	44363D	2.3	57.8	1.5	85.8	-	-	22.8	8.7	0.3899	1.58	3.53	
		0.05	2.24	0.06	3.35	-	-						

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952355733
Inside diameter	41.275 mm
Outside diameter	92.075 mm
Thickness	55.562 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE