

## Tapered roller bearing 398-394D-TIMKEN - 398-394D-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/398-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Factor <sup>(4)</sup>	
mm	mm	mm	mm	C <sub>10</sub>	N	C <sub>0</sub>	N	C <sub>10</sub>	N	C <sub>0</sub>	K
50.800	110.000	52.388	46.838	32000	17000	0.40	1.58	2.50	25600	17800	4400
2.9300	4.3307	2.0625	1.8125	38700	18700				5700	3970	10000

  

Part Number		Dimensions						Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>f</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>h</sub>	Backing Shoulder Dia. D <sub>s</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>			
398	394D	0.8 0.03	62.0 2.44	0.8 0.03	104.4 4.11	-	-	50.0	21.4	0.0394	2.28 5.04		

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952356341
Inside diameter	50.8 mm
Outside diameter	110 mm
Thickness	52.388 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE