

## Tapered roller bearing 392-394D-TIMKEN - 392-394D-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/392-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Factor <sup>(4)</sup>	
mm	mm	mm	mm	C <sub>10</sub>	N	C <sub>0</sub>	N	C <sub>10</sub>	N	C <sub>0</sub>	K
61.912	110.000	52.388	46.838	32000	17000	25600	17800	4600	1000	1.45	
2.4375	4.3307	2.0625	1.8125	38700	18700	5700	2870	10000			

  

Part Number		Dimensions				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
392	394D	0.8 0.03	70.0 2.76	0.8 0.03	104.4 4.11	-	-	58.0	21.4	0.2864	1.96 4.35

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952356938
Inside diameter	61.912 mm
Inside diameter	2 7/16" inch
Outside diameter	110 mm
Outside diameter	4.331" inch
Thickness	52.388 mm
Thickness	2 1/16" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)  
02038 087 274  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE