

Drawn cup roller bearing TA6030-Z-IKO - TA6030-Z-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/ta6030-z-iko>



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
60	TA 6030 Z	191	—	—	—	—	—	—	—	—

Boundary dimensions mm		Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	f ₂ Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.	N7 Max. Min.	N	N	rpm	IRT 5030	
60	72	30	3.4	60.000 59.981	72.018 71.988	— —	66 300	139 000	5 000	IRT 5030	

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952357409
Inside diameter	60 mm
Outside diameter	72 mm
Thickness	30 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE