



## Drawn cup roller bearing TAM5030-IKO - TAM5030-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/tam5030-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**

TAM TLAM

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
50			<b>TAM</b>	<b>5030</b>	<b>178</b>					

Boundary dimensions mm	Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring			
	F <sub>w</sub>	D	C	t <sub>2</sub> Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.							
50	62	30	3.4	50.000	49.984	62.018	61.988	—	—	59 500	114 000	6 500	IRT 4530

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 50% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952357461
Inside diameter	50 mm
Outside diameter	62 mm
Thickness	30 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE