


Drawn cup roller bearing BHAM1616-IKO - BHAM1616-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bham1616-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	BHAM 1616	48	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	h ₇ Max. Min.	h ₈ Max. Min.	N	N	rpm	IRB 1216	
25.400	33.338	25.40(1.000)	3.4	25.400 25.387	33.352 33.327	26.400	44 500	15 000			

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952362038
Inside diameter	25.4 mm
Outside diameter	33.338 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE