Drawn cup roller bearing
BAM228-IKO - BAM228-IKO

https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam228-iko



IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number: Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
34.925 (1 3/8)	—	—	—	—	—	—	BAM 228	29	—	—

Boundary dimensions mm(inch) F_w	D	C	r_s Min.	Standard mounting dimensions mm: Shaft dia. h6 Max.	Shaft dia. h6 Min.	Housing bore dia. J7 Max.	Housing bore dia. J7 Min.	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(*) rpm	Assembled inner ring
34.925 (1 3/8)	41.275 (1 5/8)	12.70 (.500)	2.8	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952363035
Inside diameter	34.925 mm
Outside diameter	41.275 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE