


Tapered roller bearing 375D-374-TIMKEN - 375D-374-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/375d-374-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDI

TYPE TDI



| Bearing Dimensions | | | | Load Ratings | | | | | | | | | | |
|--------------------|--------|---------|---------------------------|-----------------------|------|-----------------------|----------------|-----------------|-----------------------|------------------|------|-----------------------|------|------|
| Bore d | O.D. D | Width T | Double Inner Ring Width B | Dynamic ^{CR} | | Factors ^{CR} | | | Dynamic ^{CR} | | | Factors ^{CR} | | |
| mm | mm | mm | mm | C ₁₀₂ | N | Y ₁ | Y ₂ | C ₉₀ | C ₅₀ | C ₁₀₀ | N | N | N | K |
| in | in | in | in | | | | | | | | klf | klf | klf | |
| 50.800 | 93.264 | 50.013 | 53.188 | 15300 | 3400 | 0.3 | 2.0 | 3.0 | 2200 | 1300 | 3500 | 3500 | 3500 | 1.73 |
| 2.000 | 3.6718 | 1.9688 | 2.0940 | | | | | | 5120 | 2970 | 8520 | 8520 | 8520 | |

| Part Number | | Dimensions | | | | Geometry Factors | | | Bearing Weight |
|-------------|-------|----------------------------|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius BH | Backing Shoulder Dia. e _s | Max Housing Fillet Radius r ^H | Backing Shoulder Dia. D _s | G ₁ | G ₂ | C ₃ | |
| | | mm | mm | mm | mm | | | | kg |
| | | in | in | in | in | | | | lbf |
| 375D | 374 | 0.8 | 92.8 | 1.3 | 89.8 | 37.6 | 15.4 | 0.0816 | 1.46 |
| | | 0.03 | 3.65 | 0.05 | 3.53 | | | | 3.25 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952368443 |
| Inside diameter | 50.8 mm |
| Outside diameter | 93.264 mm |
| Thickness | 50.013 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE