

## Needle roller bearing BRI122412-IKO - BRI122412-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri122412-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$ <sup>(1)</sup> $S$
19.050 ( $\frac{3}{4}$ )	<b>BRI 122412</b>	102	19.050 ( $\frac{3}{4}$ )	38.100 (1 $\frac{1}{2}$ )	19.050 ( $\frac{3}{4}$ )	19.300	25.400 (1) ) 0.3
Standard mounting dimensions mm		ISO system load rating $C$	Specific load rating $C_0$	Allowable rotational speed <sup>(2)</sup>	Assembled inner ring		
$d_s$	$D_s$	$f_{st \max}$ <sup>(3)</sup>	N	N	LRB 121612		
Min.	Max.	Max.	N	N	rpm		
24	24.4	32.9	1	25 300	31 900	16 000	LRB 121612

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952375212
Inside diameter	19.05 mm
Inside diameter	3/4" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	19.3 mm
Thickness	0.76" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE