


## Needle roller bearing GBRI264116-IKO - GBRI264116-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri264116-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>41.275</b> (1 5/8)	<b>GBRI 264116</b>	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i> N	Static load rating <i>C<sub>0</sub></i> N	Allowable rotational speed (°) rpm	Assembled inner ring <b>LRBZ 263216</b>
<i>d<sub>a</sub></i>	<i>D<sub>a</sub></i>	<i>r<sub>as max</sub></i> (°)	<i>r<sub>as max</sub></i>				
Min. 48	Max. 49	Max. 59.2	1	63 100	130 000	3 000	

Notes: (°) Maximum permissible corner radius of the housing.  
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377537
Inside diameter	41.275 mm
Outside diameter	65.088 mm
Thickness	25.65 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE