


## Needle roller bearing GBR607632-IKO - GBR607632-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbr607632-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			F <sub>o</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>95.250</b> (3 3/4)	<b>GBR 607632</b>	1 420	95.250 (3)	120.650 (4 7/8)	50.800 (2)	112.6	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
228 000	522 000	1 600					

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377667
Inside diameter	95.25 mm
Outside diameter	120.65 mm
Thickness	50.8 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE