


Needle roller bearing GBR1284828-IKO - GBR1284828-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/gbri284828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
44.450 (1 3/4)	GBR1 284828	925	44.450 (1) 0	76.200 (3) 0	44.450 (1) 0	44.700	57.150 (2) 0

Standard mounting dimensions mm		Basic dynamic load rating C ₀	Limiting static rating C ₀	Allowable rotational speed (1) rpm	Assembled inner ring		
d _a	D _a						
Min.	Max.	Min.	Max.				
52.5	55	69.2	1.5	133 000	276 000	2 500	LRBZ 283628

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377889
Inside diameter	44.45 mm
Inside diameter	1 3/4" inch
Outside diameter	76.2 mm
Outside diameter	3" inch
Thickness	44.45 mm
Thickness	1 3/4" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE