

## Needle roller bearing RNA49-14-U-IKO - RNA49-14-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/rna49-14-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
<b>18</b>	---	<b>RNA 49/14U</b>	---	---	19.7	18	26	13	0.3
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (1)						
	N	N	rpm						
Notes (1)	24	9 260	10 800	11 000					
Remarks:	1. Minimum allowable value of chamfer dimension $r$ . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole. 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.								

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952378848
Inside diameter	18 mm
Outside diameter	26 mm
Thickness	13 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE