

Needle roller bearing RNA6915-U-IKO - RNA6915-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/rna6915-u-iko>

I K O

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
85	—	—	—	RNA 6915U	960	85	105	54	1
Standard mounting diameter D_s Max. mm	N	N	N	N					
Basic dynamic load rating C	128 000	299 000	299 000	2 000					
Basic static load rating C_0									
Allowable rotational speed (2)									

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379654
Inside diameter	85 mm
Outside diameter	105 mm
Thickness	30 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE