

Needle roller bearing RNA6916-U-IKO - RNA6916-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/rna6916-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
90	—	—	—	RNA 6916U	1 010	90	110	54	1
Standard mounting diameter D_s Max. mm									
	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm						
	105	132 000	317 000	2 000					

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379692
Inside diameter	90 mm
Outside diameter	110 mm
Thickness	54 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE