


Roller bearing

NNTR65X160X75-2ZL-INA - NNTR65X160X75-2ZL-INA

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nntr65x160x75-2zl-ina>

Yoke type track rollers NNTR65X160X75-2ZL
Full complement roller set, axial guidance, central rib, sealing shields with lamellar ring on both sides



| | |
|----------------------|--|
| d | 65 mm |
| D | 160 mm Tolerance: h10 |
| B | 75 mm |
| C | 3 Number of lubrication holes |
| C | 73 mm |
| D ₁ | 103 mm |
| d ₂ | 62 mm |
| d ₃ | 5 mm |
| R | 10000 mm Curvature radius |
| F _{1 and 2} | 2 mm |
| f _{max} | 3 mm |
| m | 8,6 kg Mass |
| C _{dyn} | 265000 N Effective dynamic load rating as track roller (radial) |
| C _{stat} | 395000 N Effective static load rating as track roller (radial) |
| F _{dyn} | 350000 N Permissible dynamic radial load |
| F _{stat} | 395000 N Permissible static radial load |
| C _{fat} | 50000 N Fatigue limit load |
| n _{0.2} | 700 1/min Speed (with continuous operation and grease lubrication) |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | INA |
| N° Ean13 | 4047643241250 |
| Inside diameter | 65 mm |
| Outside diameter | 160 mm |
| Thickness | 75 mm |
| Weight | 8850 g |
| Dynamic load | 270 kN |
| Static load | 400 kN |
| Packaging | - |
| Standard | - |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE