

Needle roller bearing NA4900-U-IKO - NA4900-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4900-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
10	—	NA 4900U	—	—	24.5	10	22	13	14

r_s min (¹⁾)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.	D_a Max.				
0.3	14	12	13	20	8 080	8 490	14 000	LRTZ 101414

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381060
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	14 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE