

Needle roller bearing NA4902-U-IKO - NA4902-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
15	—	NA 4902U	—	—	36	15	28	13	14

r _s mm	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		Min.	Max.	Max.			
0.3	20	17	19	26	9 570	11 600	9 500

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381121
Inside diameter	15 mm
Inside diameter	0.591" inch
Outside diameter	28 mm
Outside diameter	1.102" inch
Thickness	14 mm
Thickness	0.551" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE