


## Needle roller bearing NA6903-U-IKO - NA6903-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6903-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>17</b>	—	—	—	—	<b>NA 6903U</b>	68.5	17	30	23	24
$r_s$ min ( <sup>1)</sup> ) mm	Standard mounting dimensions mm				Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring			
	$F_w$	$d_s$		$D_s$						
0.3	22	19	21	28	19 800	30 600	BRTZ 172224			

Note<sup>(1)</sup> Minimum allowable value of diameter dimension  $r$   
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381206
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	24 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE