

## Needle roller bearing NA4906-U-IKO - NA4906-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4906-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>30</b>	—	<b>NA 4906U</b>	—	—	106	30	47	17	18

r <sub>s</sub> min <sup>(1)</sup> mm	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRTZ 303518
		Min.	Max.	Max.			
0.3	35	32	34	45	21 500	28 400	5 500

Note(1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381381
Inside diameter	30 mm
Outside diameter	47 mm
Thickness	18 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE