

## Needle roller bearing NA6911-U-IKO - NA6911-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6911-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>55</b>	—	—	—	—	<b>NA 6911U</b>	730	55	80	45	46

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub>	Basic dynamic load rating C	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	D <sub>s</sub> Max.				
1	63	60	61	75	89 400	171 000	3 000	LRTZ 556346

Note(1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: The outer ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381633
Inside diameter	55 mm
Inside diameter	2.165" inch
Outside diameter	80 mm
Outside diameter	3.15" inch
Thickness	46 mm
Thickness	1.811" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE