

Needle roller bearing NA6913-UU-IKO - NA6913-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6913-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
65	—	—	NA 6913UU	—	845	65	90	45	46

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.				
1	72	70	70.5	85	97 400	200 000	LRTZ 657246

Note(1) Minimum allowable value of shaft dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381725
Inside diameter	65 mm
Outside diameter	90 mm
Thickness	46 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE