

## Needle roller bearing NA4914-U-IKO - NA4914-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4914-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>70</b>	—	<b>NA 4914U</b>	—	—	770	70	100	30	31

r <sub>s</sub> min ( <sup>1</sup> )	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1	80	75	78	95	76 900	143 000	2 500	LRTZ 708031

Note<sup>(1)</sup> Minimum allowable value of diameter dimension r  
 Note<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: The outer ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381749
Inside diameter	70 mm
Outside diameter	100 mm
Thickness	31 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE