

Needle roller bearing NA6914-U-IKO - NA6914-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6914-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
70	—	—	—	—	NA 6914U	1 400	70	100	54	55

r _s min mm	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.	D _s Max.				
1	80	75	78	95	124 000	281 000	2 500	LRTZ 708055

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381756
Inside diameter	70 mm
Inside diameter	2.756" inch
Outside diameter	100 mm
Outside diameter	3.937" inch
Thickness	55 mm
Thickness	2.165" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE