

Needle roller bearing NA6915-UU-IKO - NA6915-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6915-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
75	—	—	NA 6915UU	—	1 480	75	105	54	55

r _s min (°)	F _w	Standard mounting dimensions mm			Basic rating C ₀	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.	D _s Max.				
1	85	80	83	100	128 000	299 000	2 000	LRTZ 758555

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381800
Inside diameter	75 mm
Inside diameter	2.953" inch
Outside diameter	105 mm
Outside diameter	4.134" inch
Thickness	55 mm
Thickness	2.165" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE