

Needle roller bearing NA4917-UU-IKO - NA4917-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4917-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
85	NA 4917UU	—	—	—	1 300	85	120	35	36

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
		d _s Min.	d _s Max.					
1.1	100	91.5	98	113.5	103 000	225 000	1 900	LRTZ 8510036

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381855
Inside diameter	85 mm
Outside diameter	120 mm
Thickness	36 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE