

## Needle roller bearing NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4918-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	NA 4918UU	—	—	—	1 360	90	125	35	36

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.					D <sub>s</sub> Min.
1.1	105	96.5	103	118.5	106 000	238 000	1 800	LRTZ 9010536

Notes: (1) Minimum allowable value of outer diameter r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381893
Inside diameter	90 mm
Outside diameter	125 mm
Thickness	36 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE