

Needle roller bearing NA6919-U-IKO - NA6919-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na6919-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
95	—	—	—	—	NA 6919U	2 600	95	130	63	64

r_s min	F_w	Standard mounting dimensions mm		Basic static load rating C_0 N	Basic dynamic load rating C_1 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.					
1.1	110	101.5	108	123.5	177 000	493 000	1 700	LRTZ 9511064

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381954
Inside diameter	95 mm
Outside diameter	130 mm
Thickness	64 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE