

## Needle roller bearing NA4922-UU-IKO - NA4922-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4922-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
110	NA 4922UU	—	—	—	2 150	110	150	40	41

r <sub>s</sub> mm	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.	N				
1.1	125	116.5	123	143.5	140 000	322 000	1 500	LRTZ 11012541

Note(1) Minimum allowable value of diameter dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382005
Inside diameter	110 mm
Outside diameter	150 mm
Thickness	41 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE