

Needle roller bearing NA4926-U-IKO - NA4926-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4926-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
130	—	NA 4926U	—	—	4 080	130	180	50	51

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					
1.5	150	138	148	172	206 000	511 000	1 300	LRTZ 13015051

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382036
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	51 mm
Thickness	2.008" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE