

## Needle roller bearing BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri102216-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>15.875</b> ( $\frac{3}{4}$ )		<b>BRI 102216 U</b>	113.5	15.875 ( $\frac{3}{4}$ )	34.925 (1 $\frac{3}{4}$ )	25.400 (1 )	25.650	

  

$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 101416 B
	Min.	Max.	Max. as max. <sup>(*)</sup>				
<b>22.225</b> ( $\frac{7}{8}$ )	21	21.2	29.7	21 600	26 900	9 000	

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382517
Inside diameter	15.875 mm
Outside diameter	34.925 mm
Thickness	25.4 mm
Weight	150 g
Packaging	-
Standard	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE