


Needle roller bearing BRI122416-UU-IKO - BRI122416-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri122416-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
19.050 (3/4)	BRI 122416 UU		127	19.050 (3/4)	38.100 (1 1/2)	25.400 (1)	25.650	
F _w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
25.400 (1)	24	24.4	32.9	0.6	23 600	31 300	8 000	LRBZ 121616 B

Notes: (*) Minimum allowable value of diameter dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382531
Inside diameter	19.05 mm
Outside diameter	38.1 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE