

Needle roller bearing BRI223520-UU-IKO - BRI223520-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri223520-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
34.925 (1 3/8)	BRI 223520 UU		275	34.925 (1 3/8)	55.562 (2 1/8)	31.750 (1 1/4)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 222620 B	
	Min.	Max.	Max.					
	40.2	40.2	48.3	44 800	70 900	4 500		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382623
Inside diameter	34.925 mm
Outside diameter	55.562 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE