

## Needle roller bearing BRI284828-UU-IKO - BRI284828-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri284828-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>44.450</b> (1 3/4)	<b>BRI 284828 UU</b>		<b>904</b>	<b>44.450 (1 3/4)</b>	<b>76.200 (3 )</b>	<b>44.450 (1 3/4)</b>	<b>44.700</b>	
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
<b>57.150 (2 1/4)</b>	<b>52.5</b>	<b>55</b>	<b>69.0</b>	<b>1.5</b>	<b>90 300</b>	<b>158 000</b>	<b>3 500</b>	<b>LRBZ 283628 B</b>

Notes: (\*) Minimum allowable value of diameter dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382708
Inside diameter	44.45 mm
Outside diameter	76.2 mm
Thickness	44.45 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE