

## Needle roller bearing BRI406028-U-IKO - BRI406028-U-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri406028-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>63.500</b> (2 1/2)		<b>BRI 406028 U</b>	1 065	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)	44.700
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
76.200 (3 )	71	73	105 000	211 000	2 500	<b>LRBZ 404828 B</b>	

Notes: (\*) Minimum allowable value of diameter dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382760
Inside diameter	63.5 mm
Outside diameter	95.25 mm
Thickness	44.45 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE