


Needle roller bearing BRI406028-UU-IKO - BRI406028-UU-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bri406028-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
63.500 (2 1/2)	BRI 406028 UU		1 065	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)	44.700

F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 404828 B
	Min.	Max.	Mis. as max. ^(*)				
76.200 (3)	71	73	87.0	105 000	211 000	2 500	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382777
Inside diameter	63.5 mm
Outside diameter	95.25 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE